



FM ENVIRONMENTAL LTD Package Pump Sump Options

	A	B
	Small GRP pump sump	Medium GRP pump sump
TOTAL HEIGHT	1840	2500, 2200-1350 #
INLET I.L. (below cover)	1440	1900, 1600-750 #
DIAMETER	350	600
INLET ORIENTATION	90deg to outlet ^	Variable
INTERNAL PIPEWORK *	32mm	32mm/50mm
OUTLET SIZE	2" BSP female thread	2" BSP female thread
OUTLET I.L.	500	330
ACCESS COVER	On request	Lockable hinged GRP

	C	D
	Junior substation (PE)	Senior substation
TOTAL HEIGHT	2000	2650
INLET I.L. (below cover)	1100, 1500	1100, 1500, 2000
DIAMETER	1000	1500
INLET ORIENTATION	Variable	Variable
INTERNAL PIPEWORK	50mm	50mm, 80mm, 100mm
OUTLET SIZE	Various	Various
OUTLET I.L.	675	705
ACCESS COVER	Galv. Steel (lock & lift)	Galv. Steel (lock & lift)



Guide details only – subject to change. All dimensions are approximate only. Check for availability. * Typical #Adjustable (cut –to-suit) ^ See image

FM Environmental also provide wide range of custom pumping solutions to suit larger applications and a full range of wastewater treatment options

July '09 (rev1)